

<b>Polyethylene Film</b>	Dual-Extruded
<b>UV Protection</b>	HALS
<b>Colour</b>	Light Grey / Black
<b>Thermal Properties</b>	Vicat Softening Point (1kg) 199°F
<b>Cold Crack Temperature</b>	-13°F
<b>500 microns thickness</b>	Bubble Film = 12 mil +/- 10% Back film = 9 mil +/- 10%
<b>Weight per m<sup>2</sup></b>	18oz +/- 10%
<b>Overall Bubble Width</b>	98.5 inch +/- 1%
<b>Welding Edges</b>	2 inch +/- 10%
<b>Overall Width</b>	102 inch +/- 10%
<b>Roll Diameter</b>	3.2 ft +/- 1%
<b>Roll Length</b>	295 ft +/- 2%
<b>Est. Quantity for 120m<sup>3</sup> truck</b>	8.2 ft = 156,453 ft <sup>2</sup> = 57 rolls
<b>Est. Quantity Containers</b>	20ft = 43,593 ft <sup>2</sup> = 18 rolls 40ft = 108,984 ft <sup>2</sup> = 45 rolls
<b>Packaging</b>	Packaged in Polyethylene bags
<b>Core Diameters</b>	Internal 2.99 inch/External 3.14 inch
<b>Identification</b>	Batch Identification by Q.A. slip and label showing Length/Grade
<b>Warranty</b>	10 year pro rata warranty
<b>GEOBUBBLE™ TECHNOLOGY</b>	
<b>Bubble Width x Length</b>	0.59 inch x1.18 inch
<b>Bubble Height</b>	0.21 inch
<b>No. of bubble per m<sup>2</sup></b>	1029